

Lignin as a Major Component of an Intumescent Fire Retardant System for Biopolyester

Valentin Carretier, Monica Francesca Pucci, Clément Lacoste, Arnaud Regazzi, Jean-christophe Quantin, J. Lopez-Cuesta

► To cite this version:

Valentin Carretier, Monica Francesca Pucci, Clément Lacoste, Arnaud Regazzi, Jean-christophe Quantin, et al.. Lignin as a Major Component of an Intumescent Fire Retardant System for Biopolyester. EPNOE 2021 - The 7th International Polysaccharide Conference, Oct 2021, Nantes, France. hal-03437013

HAL Id: hal-03437013 https://imt-mines-ales.hal.science/hal-03437013v1

Submitted on 9 Jun2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

LIGNIN AS A MAJOR COMPONENT OF AN INTUMESCENT FIRE RETARDANT SYSTEM FOR BIOPOLYESTER

Carretier V.*^a, Pucci M.F.^b, Lacoste C.^a, Regazzi A.^b, Quantin J-.C.^b, Lopez-Cuesta J-.M.^a

^a Polymer Composites and Hybrids (PCH), IMT Mines Ales, Ales, France ^b LMGC, IMT Mines Ales, Univ Montpellier, CNRS, Ales, France

* valentin.carretier@mines-ales.fr

This work is focused on the preparation and the optimization of a biobased intumescent fire-retardant system (IFR) which was applied to a biopolymer such as PLA. This aliphatic biopolyester is obtained from agricultural plants and is renewable and compostable in specific conditions. However, it has a poor thermal stability [1] and is very sensitive to hydrolysis [2]. In order to respect fire security standards, an IFR was elaborated using ammonium polyphosphate (APP) which is a common fire retardant and lignin which is a biobased by-product of the paper industry. Lignin has a good thermal stability and the ability to retard fire in composite materials by promoting the formation of char in association with APP [3]. The aim of the study is the optimization of the IFR and the chemical modification of lignin in order to prevent a trans-esterification between PLA and lignin that may break the polyester macromolecule.

The first part of the study shows that an optimized ratio between APP and lignin is situated around 17/3. At this ratio, the IFR is more efficient with a significant reduction of the heat release rate (HRR) and a good fire retardancy capability (Figure 1). In addition, an encapsulated APP was also tested with lignin. The encapsulant improved the flame retardancy of the biocomposite with a better dispersion in the matrix and an enhancement of the char promotion. Finally, the last part of the work was focused on the chemical modification of lignin with esterification or phosphorylation. Chemical treatments showed an improvement of the quality of thePLA/lignin interface, due to the modification of the surface properties of lignin. The incorporation of phosphorus with lignin may help the intumescent reaction and the char promotion directly on the lignin particle.

As a conclusion, lignin in association with APP was found to be efficient as IFR component for PLA, and beneficial as reinforcement for this polymer, applying adequate treatments to improve lignin surface properties and then the compatibility with PLA.al.




Figure 1: Heat release rate of different biocomposites [3]

- [1] O. Gordobil, I. Egüés, R. Llano-Ponte, and J. Labidi, *Polym. Degrad. Stab.*, vol. 108, pp. 330–338, 2014.
- [2] J. R. Rocca-Smith, N. Chau, D. Champion, C.-H. Brachais, E. Marcuzzo, A. Sensidoni, F. Piasente, T. Karbowiak, F. Debeaufort, *Food Chem.*, vol. 236, pp. 109–119, 2017.

[3] V. Carretier, J. Delcroix, M. F. Pucci, P. Rublon, and J.-M. Lopez-Cuesta, *Materials*, vol. 13, no. 11, p. 2450, 2020.